



SB-2EX-FC Industrial Case Taper - Tape Width 2"



The SB-2EX-FC is a fully-automatic top and bottom case taper that accepts boxes of the same size, fold the major and minor flaps and apply 2" or 3" wide pressure sensitive tape to both the top and bottom of cases.

SB-2EX-FC Taping Specifications

Sealer Type	Side belt, fully-automatic top and bottom case sealer
Machinery Makeup	Industrial strength 10 gauge steel, powder coated for durability
Belt Speed	72 feet/minute
Tape Speed	30 cases/minute, depending on box size and operator efficiency
Conveyor Height Adjustment	22.5" to 34.5", add 3" for casters if needed

Box Specifications

Minimum Box Size	5.0"	5.0"	5.0"
Maximum Box Size	22.0"	20.0"	22.0"
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape		
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges		
Electrical Requirements	110 VAC, 60Hz, 4.0A		
Air Requirements	60 PSI		

SB-2EX-FC Optional Accessories

3" Tape Head	Accepts 3" wide tape rolls
Casters	Rugged wheels for transportation within plant
Front Packing Table	Solid table bolts before taping system to allow for case packing

